

Constantly seeking better ways to be the best®

## **Black Pyramid Matting**

## **Typical Physical Properties**

| Physical Property      | <b>Test Method</b> | Typical Results           |
|------------------------|--------------------|---------------------------|
| Durometer, Shore A     | ASTM D2240         | $80 \pm 5$                |
| Tensile Strength       | ASTM D412          | 600 psi                   |
| Elongation             | ASTM D412          | 150%                      |
| Tear Resistance, Die C | ASTM D412          | 100 lbf/in                |
| Surface Finish         |                    | Pyramid                   |
| Back Finish            |                    | Textured Cloth Impression |
| Color                  |                    | Black                     |
| Flammability           | FMVSS 302          | Pass                      |

THE VALUES PRESENTED ARE TYPICAL AND ARE NOT INTENDED FOR SPECIFICATION PURPOSES. This information is provided without warrant, representation, inducement or license of any kind. INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE OR PURPOSE, except that is accurate to the best of MILCUT INC. knowledge or obtained from sources believed by MILCUT INC. to be accurate, and MILCUT INC. does not assume any legal responsibility for the use or reliance upon same. Customers are encouraged to conduct their own tests for suitability and conformance.