



Constantly seeking better ways to be the best®

Milspun Matting

Description:

This material is an anti-fatigue polyvinyl chloride (PVC) foam mat that has a linear rib surface texture.

Typical Physical Properties

Physical Property	Test Method	Typical Results
Durometer, Shore 00	ASTM D2240	65
Abrasion Resistance	ASTM D4060	≤ 1.0 gram loss
Compression	ASTM D1667	25% @ 7 psi
Resiliency	ASTM D2632	≥ 8%
Electrical Properties	ASTM D257	10 ¹¹ ohms
Density	ASTM D1667	17.5 lbs/ft ³
Cold Flex		Stiffens at 0°F
Flammability	D.O.C. FF 1-70	Meets
Average Weight		0.53 lbs/ft ²
Temperature Range		0° to 113°F

THE VALUES PRESENTED ARE TYPICAL AND ARE NOT INTENDED FOR SPECIFICATION PURPOSES. This information is provided without warrant, representation, inducement or license of any kind. INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE OR PURPOSE, except that is accurate to the best of MILCUT INC. knowledge or obtained from sources believed by MILCUT INC. to be accurate, and MILCUT INC. does not assume any legal responsibility for the use or reliance upon same. Customers are encouraged to conduct their own tests for suitability and conformance.